



**SPECIFICATION:**

- 1). Driving: Duty:1/16, Bias:1/5, V<sub>dd</sub>:5.0V, V<sub>lcd</sub>:3.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Blue
- 4). Operating temp.:0°C~+50°C
- 5). Storage temp.: -10°C~+60°C
- 6). Control IC: AIP31068(Or Compatible)
- 7). BACKLIGHT: EDGE,White(2DICES,ILED=30mA,V<sub>F</sub>=3.1V)
- 8). DIMENSIONS WITH MARK "\*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

VIEWING DIRECTION

1	2	3	4	5	6	7	8
VSS	VDD	V <sub>0</sub>	CSB	SCK	SDA	BLA	BLK

REVISION RECORD		REV	TC		DRAWING NO.		CHECKED BY		DRAWING BY		UNIT	GENERAL TOL:
First issue		A0	TC		SYB1602HV20-5C37BL-B5NG				JANY		mm	±0.1
					APPROVED BY		2013/09/02					
深圳市三元晶科技有限公司 Shenzhen TCC LCD Hi-Tech Co., Ltd												
2013/09/02												
											PAGE	1/1